

HS04707M



Rotary transfer machine



SERIE HS: It is the most profitable option to enter the sublimation market.

- Steel cylinder with Teflon surface to prevent rust and maintain uniform temperature.
- Effective, advanced and economical heating system.
- Industrial heating system with thermal oil.
- Cylinder rotation speed controller.
- Digital temperature controller.
- Option to change the rotation in the cylinder movement.
- Four tension rollers for the blanket.
- Work table for item-to-item applications.
- Oil level indicator to ensure the amount of oil in the cylinder.
- Automatic rollers to collect used material.
- Designed for continuous roll sublimation and item sublimation.
- Emergency stop device.
- Blanket protection alarm through limit sensors.



www.heatertex.com



sales@heatertex.com

SPECIFICATIONS

Belt width:

47" / 120 cm

Heat transfer principle:

Thermal oil

Thermal cylinder diameter:

7" / 18 cm

Power required:

4 KW - 5 KW aprox.

Frequency:

50-60 Hz

Load rollers:

3

Take rollers:

3

Current:

17A-25A at AC 220 V

Productivity:

19" up to 59" per min / 0,5 up to 1.5mts per min¹

Transfer system:

Roll to Roll and Piece to Piece

Startup time:

30 / 60 minutes aprox. ²

Dimensions:

50"x 74"x 51" / 127cm x 190cm x 130cm.

Working table:

55" x 23" / 140 cm x 60 cm ³

Weight:

1150Lb / 550Kg aprox.

Max temp:

450°F / 240°C



1. Depending on the type of work to be carried out and characteristics of the supplies used.
2. Depends on input voltage and ambient temperature.
3. The size of the table can be modified according to the client's needs for an additional charge.



www.heatertex.com



sales@heatertex.com