

HT06709A



Rotary transfer machine



SERIE HT: It is prepared to ensure continuous production in the sublimation line.

- Steel cylinder with Teflon surface to prevent rust and maintain uniform temperature.
- Effective, advanced and economical heating system.
- Industrial heating system with thermal oil.
- Cylinder rotation speed controller.
- Digital temperature controller.
- Option to change the rotation in the cylinder movement.
- Four tension rollers for the blanket.
- Work table for item-to-item applications.
- Oil level indicator to ensure the amount of oil in the cylinder.
- Automatic rollers to collect used material.
- Designed for continuous roll sublimation and item sublimation.
- Automatic blanket position correction system.
- Emergency stop device.
- Blanket protection alarm through limit sensors.



www.heatertex.com



sales@heatertex.com

SPECIFICATIONS

Belt width:

67" / 170 cm

Heat transfer principle:

Thermal oil

Thermal cylinder diameter:

9" / 23 cm

Power required:

7.7 KW

Load rollers:

3

Take rollers:

3

Air supply system:

Up to 100PSI ²

Current:

35A-40A at AC 220 V

Size of the blanket:

68"x 96" inches / 1.73m x 2.43m

Productivity:

19" up to 118" per min / 0,5 up to 3mts per min ¹

Transfer system:

Roll to Roll and Piece to Piece

Startup time:

50 / 70 minutes aprox ³

Dimensions:

64"x 98"x 82" / 165cm x 250cm x 210cm

Weight:

1750Lb / 800Kg aprox

Max temp:

450°F / 240°C

Frequency:

50 - 60 Hz

Working table:

70" x 35" / 180 cm x 90 cm ⁴



1. Depending on the type of work to be carried out and characteristics of the supplies used.
2. Required for installation.
3. Depends on input voltage and ambient temperature.
4. The size of the table can be modified according to the client's needs for an additional charge.



www.heatertex.com



sales@heatertex.com